

Echoflex Reference Guide

Elaho Recommended Cable Specifications

Overview

Echoflex recommends the following cables for low-voltage data transmission in permanently installed Elaho lighting control systems.

Recommended Cable

Wire Type	Purpose	Maximum Length	Notes
Belden 8471 *	Elaho Data Signal	500 m (1,640 ft)	A 2.5 mm ² (14 AWG) ESD Ground wire is required when control wires are not installed in grounded metal conduit
Category 5 or 6	Elaho Data Signal	305 m (1,000 ft)	Not all topologies are supported using Category 5/6 cable; careful planning is required to ensure the proper termination kits are available and the wire is pulled appropriately. Cat5 wiring may be terminated using EchoConnect Cat5 Station Termination Kit and must be installed using a bus topology. Refer to the installation guide that is provided with the Cat5 Station Termination Kit (8186A1207) for information to terminate Cat5 wiring.
1.5 mm ² (16 AWG) (typically black/red wire pair)	Auxiliary Power 24 VDC		Refer to the related user documentation for details about whether there is a requirement for Auxiliary Power.

*Echoflex highly recommends use of Belden 8471 (or equivalent) as the preferred cable type for EchoConnect data signal.

Compatible Substitutions

The following cable types are acceptable substitutions for the recommended cable.

Manufacturer	Model	Cable Jacket Plenum Rating
Advanced Digital	911602	Plenum
	11602R 6602K2	Non-Plenum
Alpha Wire	1899C	Non-Plenum
Belden	8471 8473 85102 9487 2412 (Ethernet) 1351A (Ethernet) 1533R (Ethernet)	Non-Plenum
Coleman Cable	94762	Non-Plenum
Connect-Air	W161P-2062B	Plenum
	W161P-1145LK	Non-Plenum
General Cable (Carol)	C8861	Non-Plenum
	C8621 81333XX (Ethernet)	Plenum

Echoflex Reference Guide

Recommended Cable

Manufacturer	Model	Cable Jacket Plenum Rating
Lake Cable	PF162CT19-ECH	Plenum
	162CPT19	Non-Plenum
Manufacturer	Model	Cable Jacket Plenum Rating
Liberty Wire and Cable	16-2C-VAN 16-2C 24-4P-L5HT (Ethernet)	Non-Plenum
	16-2C-P 16-2CP-BLK	Plenum
REMEE	900985	Non-Plenum
TMB	PCLP1PTPB	Plenum
	PCLP1PT PCLP2PT	Non-Plenum
West Penn	25225B	Plenum

A complete listing of substitute cables is provided on the ETC website. See etcconnect.com/Support/Cable-Cross-Database.