



GENERAL INFORMATION

Having the lights on in an already well-lit area means wasted energy and bigger electrical bills. Light Sensors are the sensible way to lower energy expenditures and meet energy codes. Light Sensors have a neutral look that easily blends into their surroundings. The sensors are ready to go in their standard form, or you can detach the sensor's RemoLux head to use as a remote sensor. It is perfect for atriums and other spaces with high ceilings. The Light Sensor can also be installed indoors or outdoors.

APPLICATIONS

- Houses of worship
- Education
- Hospitality
- Healthcare facilities
- Office buildings
- Conference rooms
- Meeting rooms
- Retail

FEATURES

- Sensor Controller with or without integrated Light Sensor
- RemoLux: Light Sensor can be mounted within controller housing or remotely
 - Remote sensors connect using Belden 8471 or two #16AWG wires
 - Filler included for remote-head applications
- DualLux: Supports up to two sensors to average light levels in large areas
- Single Light Sensor for indoor, outdoor and atrium use
- Configurable to activate or deactivate any controller
- Two-wire, topology-free bus for power and communication
- Each sensor counts as one station with up to two light heads
- Available in white and black
- Supports switched and dimming daylight harvesting
- Multi Space Preset functionality

GENERAL

- UL and cUL LISTED
- CE Marked
- CA Title 24 compliant

ORDERING INFORMATION

Light Sensor

MODEL	DESCRIPTION
ELS	Light Sensor with Controller
ELSC	Light Sensor Controller Only
ELSH	Light Sensor Head Only

Note: Sensors come standard in pure white (RAL9010). Add -4 to the end of any model number for black (RAL9004)

Power Requirements

Bus Power:	One unit of control power
Auxiliary Power:	Not required

SPECIFICATIONS

FUNCTIONAL

- Configurable on and off set points
- Performs space raise and lower for controllers configured to the same space
- Configurable delay/offset
- Light Sensor can be mounted within controller housing or remotely; filler included for remote head applications
- Support for up to two sensors with averaging of light levels
- Single Light Sensor for indoor, outdoor and atrium use

MECHANICAL

- Constructed of injection-molded, ABS plastic in Pure White (RAL9010) or Black (RAL 9004)
- Electronics assembly and mounting plate included
- Two cantilevered configuration buttons
- No visible means of attachment
- Surface or box mountable using included mounting plate
 - Supports drywall, plaster, wood, and concrete mounting
 - Mounts to any standard electrical box (supplied by others)
 - Mounts to compressed-fiber ceilings using wire-form adapter
- Supports internal or remote mounting of light sensor
 - Remote light head mounts to any 1/2" or 3/4" knockout
- Remote Heads use conformal-coated circuit boards resistant to corrosion from moisture
 - IP65 rated when used with a weather-tight backbox

ELECTRICAL

- Controller connects via low-voltage Class 2 wiring
 - Topology-free and polarity-independent wiring over Belden 8471 or equivalent and one #14 ESD drain wire
 - Wiring may be bus, loop, homerun or any combination of these
- Up to 500 meters (1640 feet) of control wiring per system
- Supports optional Cat5/5e wiring using Belden 1583A or equivalent
 - Requires optional Cat5 termination accessories
- Remote sensors connect using two #16AWG wires up to 1000' away from controller
- UL and cUL LISTED, CE marked

ENVIRONMENTAL

- Ambient room temperature: -30 to 55°C / -22 to 130°F
- Ambient humidity: Maximum 90% non-condensing

FUNCTIONALITY

BASIC MODE FUNCTIONALITY

- Above Target Lux Event: Space Lower
- Below Target Lux Event: Space Raise

CUSTOM MODE FUNCTIONALITY

(Requires Programming With ElahoAccess® Mobile App and additional connection hardware)

- Switched Mode Bright Events Supported:
 - Preset Activate*
 - Zone Set to Level
 - Space Off*
 - Space Set to Level
- Switched Mode Dark Events Supported:
 - Preset Activate*
 - Zone Set to Level
 - Space Off*
 - Space Set to Level
- Dimmed Mode Space Control:
 - Space Raise
 - Space Lower
- Dimmed Mode Single Zone Control:
 - Zone Raise
 - Zone Lower
- Dimmed Mode Dual Zone Control:
 - Zone 1 Raise
 - Zone 1 Lower
 - Zone 2 Percentage Raise
 - Zone 2 Percentage Lower

*Multi Space capable - allowing for presets to be recalled in multiple spaces from a single control

ELAHO FAMILY PRODUCTS

Bus Power Supplies

MODEL	DESCRIPTION
E-SPS	6U Room Station Power Supply, Knockout Mount
E-SPS-DIN	16U DIN rail Station Power Supply with 24V Aux
E-SPM	16U DRd Station Power Module
E-SPM-A	16U DRd Station Power Module with 24V Aux
E-SPM-RM	16U Rack-Mount Station Power Module Aux
E-SPM-RM-A	16U Rack-Mount Station Power Module 24V Aux
E-SPM-WM	16U Wall-Mount Station Power Module
E-SPM-WM-A	16U Wall-Mount Station Power Module 24V Aux
E-APS	24V Aux Power Supply, Knockout Mount

ElahoTouch

MODEL	DESCRIPTION
ETS	ElahoTouch Controller

Elaho Stations

MODEL	DESCRIPTION
E1001	Inspire One Button Station
E1002	Inspire Two Button Station
E1004	Inspire Four Button Station
E1006	Inspire Six Button Station
E1008	Inspire Eight Button Station
E1104	Inspire Four Button with Fader Station
EPS05	Preset Station - 5 Button
EPS10	Preset Station - 10 Button
EPSLO	Lockout Station
E-ATC	TimeClock

Elaho Responsive Controls

MODEL	DESCRIPTION
ELS	Light Sensor
EOCC	Ceiling-Mount PIR Occupancy Sensor
EVAC	Ceiling-Mount PIR Vacancy Sensor
E-DOC-C	Ceiling-Mount Dual Tech Occupancy Sensor
E-DVAC-C	Ceiling-Mount Dual Tech Vacancy Sensor
E-DOC-W	Wall-Mount Dual Tech Occupancy Sensor
E-DVAC-W	Wall-Mount Dual Tech Vacancy Sensor
E-DOC-SM1	Switch-Mount Dual Tech Sensor - One Button
E-DOC-SM2	Switch-Mount Dual Tech Sensor - Two Button

Elaho Interfaces

MODEL	DESCRIPTION
EACC	ElahoAccess Interface
EEB	Expansion Bridge
EDMXC	DMX Scene Controller
EEL	Elaho-Echoflex Interface
ECII	Contact Input Interface
ECOI	Contact Output Interface
EDRI	Demand Response Interface
EBI	BACnet Interface

Zone Controllers

MODEL	DESCRIPTION
ERC-G2	One Zone Relay Controller
EDRC-G2	Two Zone Relay Controller
ELD-G2	One Zone 0-10V Controller
EDLD-G2	Two Zone 0-10V Controller
ESSC-G2	One Zone SmartSpace Controller
EDSSC-G2	Two Zone SmartSpace Controller
ELVD-G2	600-Watt Phase Adaptive Dimmer
ELVD-277-G2	600-Watt Phase Adaptive Dimmer- 277V

Room Controllers


MODEL	DESCRIPTION
ERMCT4-G2	Four Zone Room Controller
ERMCT4-G2	Four Zone Room Controller with TimeClock
ERMCT8-G2	Eight Zone Room Controller
ERMCT8-G2	Eight Zone Room Controller with TimeClock

Panel Products


MODEL	DESCRIPTION
ERP	Elaho Relay Panel Mains Feed
ERP-FT	Elaho Relay Panel Feed Through

SAMPLE SYSTEMS

SMALL SYSTEM



CONFERENCE ROOM



PHYSICAL




Light Sensor Dimensions*

MODEL	DIAMETER		DEPTH	
	in	mm	in	mm
ELS/ ELSC	4.50	114	1.40	36
ELSH	1.60	41	0.66	17




Light Sensor Weights*

MODEL	WEIGHT		SHIPPING WEIGHT	
	oz	g	oz	g
ELS	3	76.5	9	255.1
ELSC	3	76.5	9	235.3
ELSH	1	28.3	7	178.6

*Weights and dimensions typical



SHOWN WITHOUT INCLUDED THREADED EXTENDER



SHOWN WITH INCLUDED THREADED EXTENDER